

[54] WELL COMPLETION AND WORK OVER METHOD

[75] Inventor: Thomas C. Mondshine, Houston, Tex.

[73] Assignee: Texas Brine Corporation, Houston, Tex.

[*] Notice: The portion of the term of this patent subsequent to Feb. 5, 1997, has been disclaimed.

[21] Appl. No.: 874,770

[22] Filed: Feb. 3, 1978

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 735,168, Oct. 26, 1976, abandoned.

[51] Int. Cl.³ E21B 33/138

[52] U.S. Cl. 166/292; 166/305 R; 252/8.55 R

[58] Field of Search 252/8.55 R, 8.5 A, 8.5 B, 252/8.5 LC; 166/305 R, 283, 308, 292

[56] References Cited

U.S. PATENT DOCUMENTS

3,246,692	4/1966	Metler et al.	252/8.55 R
3,319,715	5/1967	Parks	252/8.55
3,675,717	7/1972	Goins et al.	166/278
3,852,201	12/1974	Jackson	252/8.5
3,986,964	10/1976	Smithey	252/8.5
3,988,246	10/1970	Hartfiel	252/8.5

4,003,838	1/1977	Jackson et al.	252/8.5
4,046,197	9/1977	Gruesbeck et al.	252/8.5
4,186,803	2/1980	Mondshine	166/292

OTHER PUBLICATIONS

Rogers, Composition and Properties of Oil Well Drilling Fluids, Third Edition, Pub. 1963, pp. 426-478 and 619-622.

Primary Examiner—Herbert B. Guynn
Attorney, Agent, or Firm—Jack W. Hayden

[57]

ABSTRACT

A well completion and workover method wherein a subterranean formation is contacted with a high density, nondamaging treating fluid which comprises a saturated, aqueous saline solution with at least one water soluble salt that is substantially insoluble in the saturated saline solution. The water soluble salt has a particle size range of about 5 microns to about 800 microns, and greater than about 5 percent of the particles are coarser than 44 microns to control the pressure in the formation; to bridge and seal off the formation; to avoid particle invasion; and also to minimize fluid loss to the formation. A minor amount of a fluid loss additive is included in the treating fluid to inhibit loss of fluid into the formation and a minor amount of a suspension additive is included in the treating fluid to prevent settling of the water soluble salt particles in the aqueous saline solution. The aqueous saline solution should have a density of at least about 10 pounds per gallon.

5 Claims, 2 Drawing Figures